

HTS系列風車馬達規格表

機型	電壓	相數	電流	功率	頻率	轉速	噪音	風壓	風量
HTS-403	100-120V	1 ϕ	0.9A	45W	50/60HZ	2800/3450r.p.m	50/54db	8.2/9.3mm.Aq	2.7/2.9M ³ /min
	200-240V	1 ϕ	0.44A	45W	50/60HZ	2800/3450r.p.m	50/54db	8.2/9.3mm.Aq	2.7/2.9M ³ /min
HTS-503	200-240V	1 ϕ	0.7-0.75A	90W	50/60HZ	2800/3450r.p.m	50/54db	8.2/9.3 mm.Aq	2.7/2.9M ³ /min
	200-240V	3 ϕ	0.26-0.3A	90W	50/60HZ	2800/3450r.p.m	50/54db	8.2/9.3 mm.Aq	2.7/2.9M ³ /min
	380-415V	3 ϕ	0.15-0.2A	90W	50/60HZ	2800/3450r.p.m	50/54db	8.2/9.3 mm.Aq	2.7/2.9M ³ /min
	440-480V	3 ϕ	0.13-0.16A	90W	50/60HZ	2800/3450r.p.m	50/54db	8.2/9.3 mm.Aq	2.7/2.9M ³ /min
	Δ 220V/Y380V	3 ϕ	Δ 0.26A/Y0.15A	90W	50/60HZ	2800/3450r.p.m	50/54db	8.2/9.3 mm.Aq	2.7/2.9M ³ /min
HTS-602	200-240V	1 ϕ	0.7-0.75A	90W	50/60HZ	2800/3450r.p.m	63/69db	12.9/14.6mm.Aq	2.7/2.9M ³ /min
	200-240V	3 ϕ	0.26-0.3A	90W	50/60HZ	2800/3450r.p.m	63/69db	12.9/14.6mm.Aq	2.7/2.9M ³ /min
	380-415V	3 ϕ	0.15-0.2A	90W	50/60HZ	2800/3450r.p.m	63/69db	12.9/14.6mm.Aq	2.7/2.9M ³ /min
	440-480V	3 ϕ	0.13-0.16A	90W	50/60HZ	2800/3450r.p.m	63/69db	12.9/14.6mm.Aq	2.7/2.9M ³ /min
	Δ 220V/Y380V	3 ϕ	Δ 0.26A/Y0.15A	90W	50/60HZ	2800/3450r.p.m	63/69db	12.9/14.6mm.Aq	2.7/2.9M ³ /min
HTS-702	200-240V	1 ϕ	0.96-1.15A	200W	50/60HZ	2800/3450r.p.m	68/74db	18.7/22.6 mm.Aq	4.6/5.1M ³ /min
	200-240V	3 ϕ	0.5-0.64A	200W	50/60HZ	2800/3450r.p.m	68/74db	18.7/22.6 mm.Aq	4.6/5.1M ³ /min
	380-415V	3 ϕ	0.3-0.42A	200W	50/60HZ	2800/3450r.p.m	68/74db	18.7/22.6 mm.Aq	4.6/5.1M ³ /min
	440-480V	3 ϕ	0.28-0.35A	200W	50/60HZ	2800/3450r.p.m	68/74db	18.7/22.6 mm.Aq	4.6/5.1M ³ /min
	Δ 220V/Y380V	3 ϕ	Δ 0.56A/Y0.3A	200W	50/60HZ	2800/3450r.p.m	68/74db	18.7/22.6 mm.Aq	4.6/5.1M ³ /min
	各電壓皆可製作強力型風車			250W	50/60HZ	2800/3450r.p.m	73/78db	20.0/25.2 mm.Aq	7.2/8.1 M ³ /min
HTS-802	200-240V	3 ϕ	0.75-0.9A	250W	50/60HZ	2800/3450r.p.m	73/78db	20.0/25.2 mm.Aq	7.2/8.1 M ³ /min
	380-415V	3 ϕ	0.44-0.53A	250W	50/60HZ	2800/3450r.p.m	73/78db	20.0/25.2 mm.Aq	7.2/8.1 M ³ /min
	440-480V	3 ϕ	0.4-0.47A	250W	50/60HZ	2800/3450r.p.m	73/78db	20.0/25.2 mm.Aq	7.2/8.1 M ³ /min
	Δ 220V/Y380V	3 ϕ	Δ 0.8A/Y0.53A	250W	50/60HZ	2800/3450r.p.m	73/78db	20.0/25.2 mm.Aq	7.2/8.1 M ³ /min
	各電壓皆可製作強力型風車			400W	50/60HZ	2800/3450r.p.m	76/79db	21.5/25.3 mm.Aq	13.2/15.8 M ³ /min