


PMCA

9G3B225K, A73B155J

金屬化聚丙烯膜電容器

METALLIZED POLYPROPYLENE FILM CAPACITOR



用 途/Application

- 工業用途。
- 適用於馬達變頻器。
- 適用於電梯控制；不斷電系統的 IGBT&PWM 電路。
- Industrial purpose.
- Frequency inverter for Motor.
- Most proper elevator, uninterruptible power IGBT & PWM circuit.

特 性/Specific features

- 頻率特性優良，介電損耗小，絕緣電阻高，溫度變化穩定。
- 壽命長，可靠性高。
- 擁有優良的自行復原特性。
- 外層使用阻燃性塑膠外殼(UL 94 V-0)；灌注阻燃型環氧樹脂(UL 94 V-0)，擁有良好的防火物理特性。
- Low loss, high insulation, perform for frequency and temperature changes characteristic.
- Long operating life for perform high reliability.
- Self-healing construction.
- Using non-flammable plastic case (UL94V-0) and epoxy resin (UL 94 V-0) filled.

規 格/Specifications

項目 / Item	性能/ Performance		條件/Remark
使用溫度範圍 Operating Temperature Range	-40°C ~ +85°C (+105°C)		-----
額定電壓 Rated Voltage	1250VDC		-----
耐電壓 Voltage Proof	端子間 Between Terminals	無異常 / No defect	W.V.×150% 60 秒間 W.V.×150% 60sec.
	端子外裝間 Between Terminals and case	無異常 / No defect	W.V.×200% 2~5 秒間 W.V.×200% 2 - 5sec.
絕緣電阻 Insulation Resistance	50,000Ω·F 以上 / More than 50,000Ω·F		100VDC 60 秒 100VDC 60sec.
電容量 Capacitance	1.5μF, 2.2μF		1kHz ±20%
電容量誤差 Capacitance Tolerance	±5%(J)		1kHz ±20%
介質損失角 Dissipation Factor	0.0015 以下 / 0.0015 or less		1kHz ±20%


※相關使用，請參考塑膠薄膜電容器使用注意事項。

※For handling, please refer to Guideline of special attention for the usage of plastic film capacitors.


PMCA 9G3B225K, A73B155J

尺寸/Dimensions (mm)

■ 9G3B225K



■ A73B155J



Cap. μF	1250VDC		
	L	H	T
1.5	50.0	35.5	24.5
2.2	59.0	40.0	30.0

※如有其他特殊規格需求，請聯絡我們洽詢。

※If others than above specification, please confirm to us for the information.